

ONCHAN RACEWAY

Stockcar Racing

2 Ashbourne Avenue
Braddan
Isle of Man
Tel: 01624 670649 / 629446
07624 432 232

E-mail: onchanraceway@hotmail.com
Web Site: www.onchanraceway.com

FORMULA 2 Spec. 2010

Following the recent Formula 2 drivers meeting, we decided to adopt the Brisca F2 car specifications for the 2010 season.

With the following exceptions :-

Grading will take place after every 5 meetings, roofs, wings and aerofoils can be painted in any colour, the outside contact surfaces of both front and rear bumpers need painting in your grade colour.

The Avon wide safety tyre will still be used throughout 2010, they can be softened to a durometer reading of 40, tyres will be tested randomly throughout the season.

Local drivers will have the option to use the Yokohama or other Brisca spec tyres during the Manx Open Championship, or the Formula 2 T.T. meetings. So that local and visiting drivers can compete together.

Since Brisca will be adopting the 53% inside weight rule, we have decided to return to the anti clockwise racing direction for 2010.

Car weights will be checked before the season begins, then randomly checked throughout the season.

A quick reminder of items which need attention before the start of 2010.

3mm steel plate must be welded to the top and lower chassis rails and cover the area of the drivers footwell. The plate must be fitted on both sides of the car and cover the area from the firewall to the front edge of the drivers seat.

The steel plate must not be drilled to lighten it in any way.

Wings / Aerofoils if fitted –

1. the underside of the end plates need to be in line or above the side tubes of the rollcage.
2. centre line of the wing needs to be fitted on the centre line of the car.

Maximum inside weight will be 53%. This will be checked on a random basis, before or after a race less driver. Refuelling will not be allowed if weighed after a race.

Steel fuel tanks minimum thickness 2 mm must be fitted close to the main rails, or behind the drivers seat. If fitted behind the seat a full firewall must be fitted between the tank and driver.

Battery must be fitted close to the main chassis rail.

First meeting of 2010 is planned to take place Sunday 25th April. !!!!